

PRODUCT SPECIFICATION: SPE.PROD.0008

Section 1 – GENERAL	
Product Name:	Sulphuric Acid, 98% (Select Grade)
Description:	Sulphuric acid, H ₂ SO ₄ , is a clear, oily, corrosive liquid.
Properties:	Density at 20 °C : 1,83 g/cm ³ Viscosity at 25 °C : 22 mPa.s Boiling point at 101,3 kPa : 330 °C Specific heat at 20 °C : 1,42 J/g °C Vapour pressure at 55 °C : < 1,2 Pa
Toxicity:	Has a rating of 4 according to Clinical Toxicology of Commercial Products (extremely toxic). The probable lethal dose (to humans) is 50 to 500 mg/kg of body mass. TWA OEL-RL: 1 mg/m ³
Hazards:	<p>The material is extremely corrosive to body tissue and contact with concentrated acid results in rapid destruction of tissue, causing severe burns. Ingestion may cause severe injury and can result in death. Repeated contact with dilute solution causes dermatitis. Inhalation of concentrated vapours and mists results in serious damage to lung tissue and can cause unconsciousness. Eye contact may result in serious damage and total loss of vision.</p> <p>The material is a very powerful acidic oxidizer which can ignite or even explode on contact with many materials; i.e. acetic acid, carbides, chlorates, fulminates, perchlorates, etc. It reacts exothermically with water, evolving steam. When heated the material emits highly toxic fumes. Dilute acid is corrosive to most metals with evolution of flammable hydrogen.</p>
Special Precautions:	Full protective clothing and a face shield must be worn when handling the material. Avoid ingestion, inhalation, skin and eye contact. Store away from combustibles, strong oxidising or reducing materials. Always add acid slowly to diluents.
Statutory Aspects:	UN 1830. Transported as Dangerous Good.

PRODUCT SPECIFICATION: SPE.PROD.0008

	Chemical Initiatives (Pty) Ltd: Material Safety Data Sheet. Occupational Health and Safety Act, No:85 OF 1995
--	---

Section 2 – SPECIFICATION

Appearance:	The material is a clear, oily liquid, free from visible impurities/matter and sediment.
Strength:	Not less than 98 % (m/m) as H ₂ SO ₄
Chlorides:	Not more than 10 p.p.m. (m/m) as Cl
Nitrates:	Not more than 20 p.p.m. (m/m) as NO ₃
Iron:	Not more than 20 p.p.m. (m/m) as Fe
Copper:	Not more than 1 p.p.m. (m/m) as Cu
Manganese:	Not more than 0,5 p.p.m. (m/m) as Mn
Ammonia:	Not more than 10 p.p.m. (m/m) as NH ₄
Oxidisable Impurities:	Not more than 30 p.p.m. (m/m) as SO ₂

Section 3 – TESTING XXX (CHECK)

The material is sampled and tested according to the most recent editions of the Sampling Procedures and Analytical Schedule respectively. The sample is tested to the most recent edition of the method specified.

<u>PARAMETER</u>	<u>METHOD NO.</u>
3.1 Appearance	UMBOG 54
3.2 Strength	UMBOG 54
3.3 Iron	UMBOG 54

This product is manufactured and tested at:
Umbogintwini and other traded acid facilities.

PRODUCT SPECIFICATION: SPE.PROD.0008

Section 4 – PACKING

Road Tankers

Section 5 – DOCUMENTATION

This specification is based on: Information from Umbogintwini Factory.

Section 6 – USES

As an industrial chemical

Section 7 – REASON FOR REVISION

June 2013 – New template